

Serial No.: 10/762,521
Art Unit: 3611
Examiner: LUM VANNUCCI, Lee Sin Yee
Page 2 of 11

In the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. **(Currently Amended)** A vehicle comprising:
 - a. a frame comprising a plurality of frame members;
 - b. an engine disposed on the frame;
 - c. a straddle seat disposed on the frame for accommodating a rider;
 - d. a handlebar disposed on the frame for steering the vehicle;
 - e. a front suspension disposed on the frame;
 - f. at least a front wheel disposed on the front suspension;
 - g. a rear suspension disposed on the frame, the rear suspension comprising a rear swing arm pivotally connected to the frame at a swing arm pivot axis and a shock absorber operatively disposed between the frame and the rear swing arm;
 - h. at least one rear wheel disposed on the rear swing arm; and
 - i. a continuously variable transmission operatively connecting the engine to the at least one rear wheel, the continuously variable transmission comprising a housing that comprises at least one of the plurality of frame members,
the swing arm being pivotable relative to the housing about the swing arm pivot axis.
2. **(Original)** The vehicle of claim 1, wherein the frame is a unitary structure.
3. **(Original)** The vehicle of claim 1, wherein a load transmitted to the frame by the rear swing arm is borne by the housing.
4. **(Original)** The vehicle of claim 1, wherein a load transmitted to the frame by the swing arm is borne by the housing and the rear shock absorber.
5. **(Previously Presented)** The vehicle of claim 1, wherein the continuously variable transmission further comprises a drive pulley and a driven pulley, the driven pulley comprising a centrifugal clutch and the driven pulley has a driven pulley axis.

Serial No.: 10/762,521

Art Unit: 3611

Examiner: LUM VANNUCCI, Lee Sin Yee

Page 3 of 11

6. **(Original)** The vehicle of claim 4, wherein the vehicle has only one front wheel and one rear wheel.
7. **(Original)** The vehicle of claim 4, wherein the vehicle has two front wheels and one rear wheel.
8. **(Original)** The vehicle of claim 4, wherein the vehicle has two front wheels and two rear wheels.
9. **(Original)** The vehicle of claim 4, wherein the frame members are separately manufactured.
10. **(Original)** The vehicle of claim 1, wherein the frame defines a storage bin between the handlebar and the seat that is sized to accommodate a helmet.
11. **(Currently Amended)** ~~The vehicle of claim 5~~ A vehicle comprising:
- a. a frame comprising a plurality of frame members;
 - b. an engine disposed on the frame;
 - c. a straddle seat disposed on the frame for accommodating a rider;
 - d. a handlebar disposed on the frame for steering the vehicle;
 - e. a front suspension disposed on the frame;
 - f. at least a front wheel disposed on the front suspension;
 - g. a rear suspension disposed on the frame, the rear suspension comprising a rear swing arm pivotally connected to the frame at a swing arm pivot axis and a shock absorber operatively disposed between the frame and the rear swing arm;
 - h. at least one rear wheel disposed on the rear swing arm; and
 - i. a continuously variable transmission operatively connecting the engine to the at least one rear wheel, the continuously variable transmission comprising:
 - a housing that comprises at least one of the plurality of frame members; and
 - a drive pulley and a driven pulley, the driven pulley comprising a centrifugal clutch and the driven pulley has a driven pulley axis,

Serial No.: 10/762,521

Art Unit: 3611

Examiner: LUM VANNUCCI, Lee Sin Yee

Page 4 of 11

wherein the swing arm pivot axis is substantially aligned with the driven pulley axis.

12. **(Original)** The vehicle of claim 11, wherein the driven pulley axis is coaxial with the swing arm pivot axis.

13. **(Original)** The vehicle of claim 1, wherein the housing is the lowest-most frame member.

14. **(Currently Amended)** A vehicle comprising:

- a. a frame comprising a plurality of frame members;
- b. a continuously variable transmission comprising a drive pulley, a driven pulley and a housing, the driven pulley having an axis and the housing comprising one of the plurality of frame members;
- c. a gearbox disposed proximal to the driven pulley;
- d. a centrifugal clutch operatively connected to the driven pulley, the centrifugal clutch having a center of rotation defining an axis, the axis being substantially coaxial with the driven pulley;
- e. an engine disposed on the frame;
- f. a straddle seat disposed on the frame for accommodating a rider;
- g. a handlebar disposed on the frame for steering the vehicle;
- h. a front suspension disposed on the frame;
- i. at least a front wheel disposed on the front suspension;
- j. a rear suspension disposed on the frame; [[and]]
- k. a swing arm pivotally mounted to the frame and being pivotable relative to the housing about a pivot axis; and
- l. at least a rear wheel disposed on the swing arm.

15. **(Original)** The vehicle of claim 14, wherein the gearbox is a planetary type gearbox.

16. **(Original)** The vehicle of claim 15, wherein the planetary type gearbox has a center of rotation defining an axis, the axis being substantially coaxial with the driven pulley axis.

17. **(Cancelled)**

MONTREAL 685481.1
1058247

Serial No.: 10/762,521
Art Unit: 3611
Examiner: LUM VANNUCCI, Lee Sin Yee
Page 5 of 11

18. **(Currently Amended)** ~~The vehicle of claim 14, further comprising~~ A vehicle comprising:

- a. a frame comprising a plurality of frame members;
- b. a continuously variable transmission comprising a drive pulley, a driven pulley and a housing, the driven pulley having an axis and the housing comprising one of the plurality of frame members;
- c. a gearbox disposed proximal to the driven pulley;
- d. a centrifugal clutch operatively connected to the driven pulley, the centrifugal clutch having a center of rotation defining an axis, the axis being substantially coaxial with the driven pulley;
- e. an engine disposed on the frame;
- f. a straddle seat disposed on the frame for accommodating a rider;
- g. a handlebar disposed on the frame for steering the vehicle;
- h. a front suspension disposed on the frame;
- i. at least a front wheel disposed on the front suspension;
- j. a rear suspension disposed on the frame;
- k. a swing arm pivotally mounted to the frame about a pivot axis;
- l. at least a rear wheel disposed on the swing arm; and
- m. a brake, the brake having a center of rotation defining an axis, the axis being substantially coaxial with the driven pulley.

19. **(Currently Amended)** ~~The vehicle of claim 14, further comprising~~ A vehicle comprising:

- a. a frame comprising a plurality of frame members;
- b. a continuously variable transmission comprising a drive pulley, a driven pulley and a housing, the driven pulley having an axis and the housing comprising one of the plurality of frame members;
- c. a gearbox disposed proximal to the driven pulley;
- d. a centrifugal clutch operatively connected to the driven pulley, the centrifugal clutch having a center of rotation defining an axis, the axis being substantially coaxial with the driven pulley;
- e. an engine disposed on the frame;
- f. a straddle seat disposed on the frame for accommodating a rider;

MONTREAL.685481 I
1038247

Serial No.: 10/762,521

Art Unit: 3611

Examiner: LUM VANNUCCI, Lee Sin Yee

Page 6 of 11

- g. a handlebar disposed on the frame for steering the vehicle;
- h. a front suspension disposed on the frame;
- i. at least a front wheel disposed on the front suspension;
- j. a rear suspension disposed on the frame;
- k. a swing arm pivotally mounted to the frame about a pivot axis;
- l. at least a rear wheel disposed on the swing arm; and
- m. a drive system including a drive sprocket and a driven sprocket, the drive sprocket having a center of rotation defining an axis, the axis being substantially coaxial with the driven pulley.

20. **(Original)** A vehicle comprising:

- a. a frame including a plurality of frame members;
- b. an engine disposed on the frame;
- c. a straddle seat disposed on the frame for accommodating a rider;
- d. a handlebar disposed on the frame for steering the vehicle;
- e. a front suspension disposed on the frame;
- f. at least a front wheel suspended from the front suspension;
- g. a rear suspension disposed on the frame, the rear suspension comprising a shock absorber;
- h. a storage bin disposed between the handlebar and the straddle seat that is sized to accommodate at least one helmet;
- i. a continuously variable transmission disposed on the frame, the continuously variable transmission being completely supported by the front suspension and the rear suspension;
- j. a swing arm pivotally mounted to the frame about a pivot axis; and
- k. a frame member means for transmitting power from the engine to the wheel.